



PRODUCT DATA

Brand Name: JAMB COAT P DRY

Description: JAMB COAT P DRY is a phosphate-bonded refractory coating developed for the spray maintenance of coke oven door jambs and brickwork in Coke Plants. This product is shipped in a dry, ready-to-mix form.

Physical properties shown are average values of samples taken under controlled conditions
ASTM test methods used where applicable

Maximum Service Temperature : 2600°F (1427°C)

Material Installed Weight, per Cubic Foot : 100 lbs. (approximate)

Typical Water Required for Mixing (by weight) :
Spraying 25.0%

Suggested Water Addition: 3.9% or 5.5 Quarts per 45 lb bag

Typical Chemical Analysis (%)

(Calcined Basis including Liquid Binder)

Alumina (Al ₂ O ₃)	41.7
Silica (SiO ₂)	54.2
Iron Oxide (Fe ₂ O ₃)	1.0
Titania (TiO ₂)	0.4
Lime (CaO)	0.1
Phosphorus Pentoxide (P ₂ O ₅)	0.6
Alkalis (Na ₂ O+K ₂ O)	0.8
Other	1.2

Standard Packaging: 45 lb bags

Brand Code: 3039

The properties shown on this data sheet represent typical average results using standard ASTM test methods (unless otherwise noted) conducted under controlled condition (using standard rectangular shapes), and should not be considered to be guaranteed specifications. Properties are subject to normal manufacturing statistical standard deviation ranges, and Resco Products, Inc. reserves the right to modify the properties and specifications at any time without prior notice.

RESCO PRODUCTS disclaims any express or implied warranties based on this sheet.

01/18/17 is the date that this data sheet was updated. Check with your RESCO sales representative or RESCO website to determine you have the current sheet.

One Robinson Plaza - Suite 300, 6600 Steubenville Pike, Pittsburgh, PA, 15205 Phone: 888-283-5505