



# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 9/16/2022 Revision date: 9/16/2022 Supersedes: 11/12/2019

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : DOL-Mix-R+  
CAS-No. : Mixture  
Product code : 5037  
Other means of identification : Dolomite Speciality

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory  
Recommended use : Industrial use

#### 1.3. Supplier

Resco Products, Inc.  
One Robinson Plaza, Suite 300  
6600 Steubenville Pike  
Pittsburgh, PA, 15205  
United States  
412-494-4491  
[SDS@RescoProducts.com](mailto:SDS@RescoProducts.com) - [WWW.RescoProducts.com](http://WWW.RescoProducts.com)

#### 1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300  
Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 1A H314 Causes severe skin burns and eye damage  
Carcinogenicity Category 1A H350 May cause cancer (Inhalation)  
Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger  
Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage  
H350 - May cause cancer (Inhalation)  
Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear eye protection, protective gloves, protective clothing.  
P223 - Do not allow contact with water.  
Avoid contact with the skin and the eyes  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF ON SKIN: Gently wash with plenty of soap and water.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
P260 - Do not breathe dust.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : May release smoke when heated. Combustion products include carbon monoxide, carbon dioxide, and hydrocarbon vapors.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
calcium oxide	CAS-No.: 1305-78-8	50 – 75	Skin Corr. 1A, H314
Magnesium Oxide	CAS-No.: 1309-48-4	20 – 50	Not classified

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Oil	-	1 – 5	Not classified
crystalite	CAS-No.: 14464-46-1	0.1 – 0.5	Carc. 1A, H350
quartz	CAS-No.: 14808-60-7	0.1 – 0.5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove the victim into fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Sand.
Unsuitable extinguishing media	: Do not use extinguishing media containing water.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Reactions involving a fire hazard: see "Reactivity Hazard". Do not breathe fumes from fires or vapors from decomposition.
-------------	---

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: In case of fire, use powder extinguisher, "never use water". In case of fire, never use water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Protective gloves. Safety glasses. Safety shoes. Protective clothing.
Emergency procedures	: Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment.
----------------------	--

#### 6.2. Environmental precautions

No additional information available

#### 6.3. Methods and material for containment and cleaning up

For containment	: On land, sweep or shovel into suitable containers.
Methods for cleaning up	: Collect spillage.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes. Contact lenses should be removed. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
-------------------------------	---

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store this product in a dry location where it can be protected from the elements. Protect from moisture.
Incompatible products	: Acids; reactive fluorinated, brominated, or phosphorous compounds; aluminum (may form hydrogen gas); reactive metals; organic acid anhydrides; nitro-organic compounds; interhalogenated compounds.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### DOL-Mix-R+ (Mixture)

No additional information available

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Magnesium Oxide (1309-48-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup> inhalable dust
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL (TWA) [1]	10 mg/m <sup>3</sup> respirable dust
<b>calcium oxide (1305-78-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	2 mg/m <sup>3</sup>
<b>crystalite (14464-46-1)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> respirable dust
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL (TWA) [1]	0.05 mg/m <sup>3</sup> respirable dust
<b>Oil</b>	
No additional information available	
<b>quartz (14808-60-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m <sup>3</sup> respirable dust
Remark (OSHA)	(3) See Table Z-3.
<b>8.2. Appropriate engineering controls</b>	
Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.	
<b>8.3. Individual protection measures/Personal protective equipment</b>	
<b>Personal protective equipment:</b> Avoid all unnecessary exposure.	
<b>Hand protection:</b> Wear protective gloves.	
<b>Eye protection:</b> Chemical goggles or safety glasses	
<b>Skin and body protection:</b> Wear suitable protective clothing	
<b>Respiratory protection:</b> Wear appropriate mask	

### Other information:

Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular Mixture.
Color	: brown
Odor	: Slight Petroleum Odor
Odor threshold	: No data available

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: No data available
Melting point	: > 2500 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.8 – 3
Solubility	: Reacts with water to form Ca(OH) <sub>2</sub> , Mg(OH) <sub>2</sub> , and heat.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts exothermically with water (moisture). Reacts with water to form Ca(OH)<sub>2</sub>, Mg(OH)<sub>2</sub>, and heat. Reacts with acids to form calcium salts while generating heat.

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Water, humidity.

### 10.5. Incompatible materials

Acids.

### 10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
calcium oxide (1305-78-8)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2500 mg/kg body weight (EU Method B.3: Acute toxicity (dermal), 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.04 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 15 day(s))
Skin corrosion/irritation	: Causes severe skin burns.
Magnesium Oxide (1309-48-4)	
pH	11 (10 %)

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>calcium oxide (1305-78-8)</b>	
pH	12.5 (0.13 %, 20 °C)
<b>crystalobalite (14464-46-1)</b>	
pH	6 – 7
<b>quartz (14808-60-7)</b>	
pH	6 – 7
Serious eye damage/irritation	: Assumed to cause serious eye damage
<b>Magnesium Oxide (1309-48-4)</b>	
pH	11 (10 %)
<b>calcium oxide (1305-78-8)</b>	
pH	12.5 (0.13 %, 20 °C)
<b>crystalobalite (14464-46-1)</b>	
pH	6 – 7
<b>quartz (14808-60-7)</b>	
pH	6 – 7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).
<b>quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
<b>Magnesium Oxide (1309-48-4)</b>	
Viscosity, kinematic	Not applicable (solid)
<b>calcium oxide (1305-78-8)</b>	
Viscosity, kinematic	Not applicable (solid)
Symptoms/effects after skin contact	: May cause moderate irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
<b>calcium oxide (1305-78-8)</b>	
LC50 - Fish [1]	50.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Read-across, GLP)
EC50 - Crustacea [1]	49.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, Locomotor effect)
ErC50 algae	184.57 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Read-across, GLP)
<b>12.2. Persistence and degradability</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>calcium oxide (1305-78-8)</b>	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
<b>crystalite (14464-46-1)</b>	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
<b>quartz (14808-60-7)</b>	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>12.3. Bioaccumulative potential</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>calcium oxide (1305-78-8)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>crystalite (14464-46-1)</b>	
Bioaccumulative potential	No data available.
<b>quartz (14808-60-7)</b>	
Bioaccumulative potential	No data available.
<b>12.4. Mobility in soil</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Surface tension	No data available in the literature
Ecology - soil	No data available.
<b>calcium oxide (1305-78-8)</b>	
Surface tension	No data available in the literature
Ecology - soil	No (test) data on mobility of the substance available.
<b>crystalite (14464-46-1)</b>	
Ecology - soil	No data available.
<b>12.5. Other adverse effects</b>	
No additional information available	
<b>SECTION 13: Disposal considerations</b>	
<b>13.1. Disposal methods</b>	
No additional information available	
<b>SECTION 14: Transport information</b>	
In accordance with DOT / TDG / IMDG / IATA	
<b>Department of Transportation (DOT)</b>	
Not regulated	
<b>Transportation of Dangerous Goods</b>	
Not regulated	
<b>Transport by sea</b>	
Not regulated	
<b>Air transport</b>	
Not regulated	
<b>SECTION 15: Regulatory information</b>	
<b>15.1. US Federal regulations</b>	
All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory	
<b>15.2. International regulations</b>	
<b>CANADA</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>calcium oxide (1305-78-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

# DOL-Mix-R+

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Magnesium Oxide (1309-48-4)</b> <b>crystalite (14464-46-1)</b>
Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

<b>quartz (14808-60-7)</b>
Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

<b>DOL-Mix-R+ (Mixture)</b>	
U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to <a href="http://WWW.P65Warnings.ca.gov">WWW.P65Warnings.ca.gov</a>

<b>crystalite (14464-46-1)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

<b>quartz (14808-60-7)</b>					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
calcium oxide (1305-78-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Cristobalite (14464-46-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 09/16/2022

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

<b>Full text of H-phrases</b>	
H314	Causes severe skin burns and eye damage
H350	May cause cancer

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.