

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Paco Coating Mix
 CAS-No. : Mixture
 Product code : 0211
 Other means of identification : Alumina-Silicate Speciality

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory
 Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
 One Robinson Plaza, Suite 300
 6600 Steubenville Pike
 Pittsburgh, PA 15205 - United States
 412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
 Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation
 Serious eye damage/eye irritation Category 2B H320 Causes eye irritation
 Carcinogenicity Category 1A H350 May cause cancer (Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Hazard statements (GHS US) :

: Danger
 : H315 - Causes skin irritation
 : H320 - Causes eye irritation
 : H350 - May cause cancer (Inhalation)

Precautionary statements (GHS US) :

: P280 - Wear eye protection, Dust respirator, protective gloves.
 : P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 : P332+P313 - If skin irritation occurs: Get medical advice/attention.
 : P337+P313 - If eye irritation persists: Get medical advice/attention.
 : P260 - Do not breathe dust.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
quartz	(CAS-No.) 14808-60-7	50 – 75	Carc. 1A, H350
sodium metasilicate	(CAS-No.) 6834-92-0	1 – 5	Skin Corr. 1A, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
 First-aid measures after inhalation : Allow affected person to breathe fresh air. Allow the victim to rest.
 First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse.

Paco Coating Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation : May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after eye contact : Causes eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : In case of fire, all extinguishing media allowed.

5.2. Specific hazards arising from the chemical

Fire hazard : Not flammable.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe dust.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eyes. Do not breathe dust.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Paco Coating Mix (Mixture)	
No additional information available	
sodium metasilicate (6834-92-0)	
No additional information available	
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) (mg/m ³)	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:
Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Paco Coating Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular mixture.
Color	: Gray brown
Odor	: earthy
Odor threshold	: Not applicable
pH	: No data available
Melting point	: > 2000 °F
Freezing point	: Not applicable
Boiling point	: Not applicable
Critical temperature	: Not applicable
Critical pressure	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: Not applicable
Relative evaporation rate (ether=1)	: Not applicable
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: Not Applicable
Vapor pressure at 50 °C	: Not Applicable
Relative vapor density at 20 °C	: No data available
Relative density	: 2 – 3
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: Not Applicable
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Avoid dust formation.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

sodium metasilicate (6834-92-0)

LD50 oral rat	1152 – 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral)
---------------	--

Paco Coating Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.06 mg/l (EPA OPPTS 870.1300: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

sodium metasilicate (6834-92-0)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Inhalation.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

sodium metasilicate (6834-92-0)

LC50 fish 1	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Paco Coating Mix (Mixture)

Persistence and degradability	Not established.
-------------------------------	------------------

sodium metasilicate (6834-92-0)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

quartz (14808-60-7)

Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

Paco Coating Mix (Mixture)

Bioaccumulative potential	Not established.
---------------------------	------------------

sodium metasilicate (6834-92-0)

Bioaccumulative potential	Bioaccumulation: not applicable.
---------------------------	----------------------------------

quartz (14808-60-7)

Bioaccumulative potential	No data available.
---------------------------	--------------------

12.4. Mobility in soil

sodium metasilicate (6834-92-0)

Ecology - soil	No (test) data on mobility of the substance available.
----------------	--

12.5. Other adverse effects

Effect on the global warming	: None known
Other information	: No other effects known.

Paco Coating Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Paco Coating Mix (Mixture)

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

sodium metasilicate (6834-92-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Paco Coating Mix (Mixture)

U.S. - California - Proposition 65 - Other information

This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov

quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component

State or local regulations

Quartz (14808-60-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/01/2021

Other information : Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases:

H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H320	Causes eye irritation
H335	May cause respiratory irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.