

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : PermaCast FG-GM DS  
CAS-No. : Mixture  
Product code : 7294  
Other means of identification : Basic Speciality

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory  
Recommended use : Industrial use

#### 1.3. Supplier

Resco Products, Inc.  
One Robinson Plaza, Suite 300  
6600 Steubenville Pike  
Pittsburgh, PA, 15205  
United States  
T 412-494-4491  
[SDS@RescoProducts.com](mailto:SDS@RescoProducts.com) - [WWW.RescoProducts.com](http://WWW.RescoProducts.com)

#### 1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300  
Outside USA & Canada +1 703-741-5970

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning  
Hazard statements (GHS US) : H315 - Causes skin irritation  
H320 - Causes eye irritation  
H335 - May cause respiratory irritation  
Precautionary statements (GHS US) : P280 - protective gloves, eye protection.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : May release smoke when heated. Combustion products include carbon monoxide, carbon dioxide, and hydrocarbon vapors.

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Magnesium Oxide	CAS-No.: 1309-48-4	50 – 75	Not classified
chromium(III) oxide	CAS-No.: 1308-38-9	20 – 50	Not classified
iron(III) oxide	CAS-No.: 1309-37-1	10 – 20	Not classified
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	5 – 10	Not classified

Full text of hazard classes and H-statements : see section 16

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air.
First-aid measures after skin contact	: Gently wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
-----------------------------------	-------------------------------------

#### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: In case of fire, all extinguishing media allowed.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
Hazardous decomposition products in case of fire	: This product contains a dust suppression admixture, that may give off smoke or fumes during initial heat up. These fumes include carbon monoxide, carbon dioxide, and hydrocarbons. Adequate ventilation and appropriate respiratory protection may be required.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: [In case of inadequate ventilation] wear respiratory protection. Protective gloves. Safety glasses.
Emergency procedures	: Avoid contact with skin. Avoid contact with eyes.

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment.
----------------------	--

#### 6.2. Environmental precautions

No additional information available

#### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: On land, sweep or shovel into suitable containers.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Hygiene measures	: Do not eat, drink or smoke when using this product. Wash skin thoroughly with mild soap and water.
------------------	--

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong acids.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### PermaCast FG-GM DS (Mixture)

No additional information available

##### Magnesium Oxide (1309-48-4)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	10 mg/m <sup>3</sup> inhalable dust
---------------	-------------------------------------

##### USA - OSHA - Occupational Exposure Limits

OSHA PEL (TWA) [1]	10 mg/m <sup>3</sup> respirable dust
--------------------	--------------------------------------

##### chromium(III) oxide (1308-38-9)

No additional information available

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### iron(III) oxide (1309-37-1)

#### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 5 mg/m<sup>3</sup> (Respirable fraction)

### aluminium oxide, non-fibrous (1344-28-1)

#### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA 1 mg/m<sup>3</sup> respirable dust

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear protective gloves.

#### Eye protection:

Chemical goggles or safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Granular powder.
Color	: dark gray
Odor	: Mild odour
Odor threshold	: No data available
pH	: No data available
Melting point	: > 2000 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Fire conditions may produce small amounts of hexavalent chromium and other oxidation products. May release smoke when heated. Combustion products include carbon monoxide, carbon dioxide, and hydrocarbon vapors.

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

Magnesium Oxide (1309-48-4)	
LD50 oral rat	> 5000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit, Literature study, Dermal)
chromium(III) oxide (1308-38-9)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 5.41 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
iron(III) oxide (1309-37-1)	
LD50 oral rat	> 10000 mg/kg body weight (Rat, Male, Experimental value, Oral)
LC50 Inhalation - Rat	5.05 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Causes skin irritation.

Magnesium Oxide (1309-48-4)	
pH	11 (10 %)
chromium(III) oxide (1308-38-9)	
pH	No data available in the literature
iron(III) oxide (1309-37-1)	
pH	7 (5 %)
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)

Serious eye damage/irritation : Causes eye irritation.

Magnesium Oxide (1309-48-4)	
pH	11 (10 %)
chromium(III) oxide (1308-38-9)	
pH	No data available in the literature
iron(III) oxide (1309-37-1)	
pH	7 (5 %)
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available

### Magnesium Oxide (1309-48-4)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

### chromium(III) oxide (1308-38-9)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

### iron(III) oxide (1309-37-1)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

### aluminium oxide, non-fibrous (1344-28-1)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

Symptoms/effects after inhalation : May cause respiratory irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### chromium(III) oxide (1308-38-9)

LC50 - Fish [1]	> 10000 mg/l (ISO 7346-1, 96 h, Danio rerio, Static system, Fresh water, Experimental value, GLP)
-----------------	---

#### iron(III) oxide (1309-37-1)

EC50 - Crustacea [1]	> 100 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
----------------------	--

#### aluminium oxide, non-fibrous (1344-28-1)

LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
-----------------	---

EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
----------------------	--

### 12.2. Persistence and degradability

#### Magnesium Oxide (1309-48-4)

Persistence and degradability	Not applicable.
-------------------------------	-----------------

Chemical oxygen demand (COD)	Not applicable
------------------------------	----------------

ThOD	Not applicable
------	----------------

#### chromium(III) oxide (1308-38-9)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

Chemical oxygen demand (COD)	Not applicable (inorganic)
------------------------------	----------------------------

ThOD	Not applicable (inorganic)
------	----------------------------

#### iron(III) oxide (1309-37-1)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

Chemical oxygen demand (COD)	Not applicable (inorganic)
------------------------------	----------------------------

ThOD	Not applicable (inorganic)
------	----------------------------

#### aluminium oxide, non-fibrous (1344-28-1)

Persistence and degradability	Not applicable.
-------------------------------	-----------------

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>12.3. Bioaccumulative potential</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>chromium(III) oxide (1308-38-9)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>iron(III) oxide (1309-37-1)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Bioaccumulative potential	No data available.
<b>12.4. Mobility in soil</b>	
<b>Magnesium Oxide (1309-48-4)</b>	
Surface tension	No data available in the literature
Ecology - soil	No data available.
<b>chromium(III) oxide (1308-38-9)</b>	
Surface tension	No data available in the literature
Ecology - soil	Adsorbs into the soil.
<b>iron(III) oxide (1309-37-1)</b>	
Surface tension	Not applicable (solid)
Ecology - soil	Adsorbs into the soil.
<b>aluminium oxide, non-fibrous (1344-28-1)</b>	
Surface tension	No data available in the literature
Ecology - soil	No data available.
<b>12.5. Other adverse effects</b>	
No additional information available	
<b>SECTION 13: Disposal considerations</b>	
<b>13.1. Disposal methods</b>	
No additional information available	
<b>SECTION 14: Transport information</b>	
In accordance with DOT / TDG / IMDG / IATA <b>Department of Transportation (DOT)</b> In accordance with DOT Not regulated <b>Transportation of Dangerous Goods</b> Not regulated <b>Transport by sea</b> Not regulated <b>Air transport</b> Not regulated	
<b>SECTION 15: Regulatory information</b>	
<b>15.1. US Federal regulations</b>	
<b>PermaCast FG-GM DS (Mixture)</b>	
Note	This information must be included in all SDS's that are copied and distributed for this material.

# PermaCast FG-GM DS

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### chromium(III) oxide (1308-38-9)

Subject to reporting requirements of United States SARA Section 313

### aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.
------	--

## 15.2. International regulations

### CANADA

#### Magnesium Oxide (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

#### chromium(III) oxide (1308-38-9)

Listed on the Canadian DSL (Domestic Substances List)

#### iron(III) oxide (1309-37-1)

Listed on the Canadian DSL (Domestic Substances List)

#### aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

No additional information available

## 15.3. US State regulations

### PermaCast FG-GM DS (Mixture)

U.S. - California - Proposition 65 - Other information	This product contains chromite (Cr <sup>+3</sup> ) which may in normal use, be converted chemically to a chromate (Cr <sup>+6</sup> ) hexavalent chrome, a chemical known to the State of California to cause cancer.
--	---

Component	State or local regulations
Magnesium Oxide (1309-48-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
chromium(III) oxide (1308-38-9)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
iron(III) oxide (1309-37-1)	U.S. - New Jersey - Right to Know Hazardous Substance List
aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 5/20/2024

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

### Full text of H-phrases

H315	Causes skin irritation
H320	Causes eye irritation
H335	May cause respiratory irritation

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.