

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/15/2015 Revision date: 8/9/2024 Supersedes: 7/28/2021

SECTION 1: Identification				
1.1. Identification				
Product form Product name CAS-No. Product code Other means of identification	: Mixture : Rescocast 17EPC : Mixture : 0306 : Alumina-Silicate Ce	ement Bonded Castable		
1.2. Recommended use and restrictions or				
Use of the substance/mixture	: Refractory			
Recommended use	: Industrial use			
1.3. Supplier				
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 <u>SDS@RescoProducts.com</u> - <u>WWW.RescoProducts</u>	<u>.com</u>			
1.4. Emergency telephone number				
Emergency number		Y (CHEMTREC) USA &	Canada 1-800-4	124-9300
	Outside USA & Car	nada +1 703-741-5970		
SECTION 2: Hazard(s) identification				
2.1. Classification of the substance or mix	ture			
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H3 <sup>-</sup> H32 H35	20 Causes eye		n)
2.2. GHS Label elements, including precau	tionary statements			
GHS US labeling Hazard pictograms (GHS US)				
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	P305+P351+P338 contact lenses, if pr P332+P313 - If skin	irritation cancer (Inhalation) otection, Dust respirator, - IF IN EYES: Rinse caut esent and easy to do. Co n irritation occurs: Get me irritation persists: Get m	iously with wate ontinue rinsing. edical advice/atte	r for several minutes. Remove ention.
2.3. Other hazards which do not result in c	lassification			
No additional information available				
2.4. Unknown acute toxicity (GHS US)				
No additional information available				
SECTION 3: Composition/Information	on ingredients			
3.1. Substances				
Not applicable				
3.2. Mixtures				
Name		Product identifier	%	GHS US classification
Calcium Aluminate Cement		CAS-No.: 65997-16-2	20 – 50	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
cristobalite		CAS-No.: 14464-46-1	10 – 20	Carc. 1A, H350
quartz		CAS-No.: 14808-60-7	5 – 10	Carc. 1A, H350
aluminium oxide, non-fibrous		CAS-No.: 1344-28-1	5 – 10	Not classified
	ENI (En	alish US)		1/

### Safety Data Sheet

Full text of hazard classes and H-statements : see s	ection 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	<ul> <li>Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).</li> </ul>
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact First-aid measures after eye contact	<ul> <li>Gently wash with plenty of soap and water.</li> <li>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present</li> </ul>
Thist-aid measures and eye contact	and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects	
Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause
	cancer by inhalation.
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Causes skin irritation. : Causes eye irritation.
4.3. Immediate medical attention and speci	
No additional information available	······································
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing	n media
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chem	nical
Fire hazard	: Not flammable.
5.3. Special protective equipment and prec	autions for fire-fighters
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measure	res
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel	. Do not broothe dust Avoid contract with align and avon
Emergency procedures 6.1.2. For emergency responders	: Do not breathe dust. Avoid contact with skin and eyes.
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment	• •
Methods for cleaning up 6.4. Reference to other sections	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
See Heading 8. Exposure controls and personal pro	tection
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust.
Hygiene measures	<ul> <li>Avoid contact with skin and eyes. Do not breathe dust.</li> <li>Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.</li> </ul>
7.2. Conditions for safe storage, including	
Storage conditions	: Store this product in a dry location where it can be protected from the elements.
Incompatible products	: Strong bases. Strong acids.
SECTION 8: Exposure controls/person	al protection
8.1. Control parameters	
Rescocast 17EPC (Mixture)	
No additional information available	

### Safety Data Sheet

Calcium Aluminate Cement (65997-16-2)         No additional information available         Oristobalite (14464-46-1)         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA         OSHA PEL (TWA)[1]         IUSA - ACGH - Occupational Exposure Limits         OSHA PEL (TWA)[1]         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA         Quartz (14808-60-7)         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA         Quartz (14808-60-7)         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA         Quartz (14808-60-7)         USA - ACGH+ Occupational Exposure Limits         ACGH OEL TWA         USA - Oscupational Exposure Limits
No additional information available         cristobalite (14464-46-1)         USA - ACGH+ Occupational Exposure Limits         ACGIH OEL TWA         USA - No CHA - Occupational Exposure Limits         OGSHA PEL (TWA) [1]         10.05 mg/m² respirable dust         atuminium oxide, non-fibrous (1344-28-1)         USA - ACGH - Occupational Exposure Limits         ACGIH OEL TWA         Quartz (14808-60-7)         USA - OSHA - Occupational Exposure Limits         ACGIH OEL TWA         Adopted Value, Respirable fraction)         USA - ACGH - Occupational Exposure Limits         ACGIH OEL TWA         Adopted Value, Respirable fraction)         USA - ACGH - Occupational Exposure Limits         Local name       0.025 mg/m² respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m² respirable dust         Remark (OSHA)       0.026 mg/m² respirable dust         B.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Wear sprotective clothing     <
USA - ACGH*-Occupational Exposure Limits       0.025 mg/m³ respirable dust         USA - OSHA - Occupational Exposure Limits       0.06 mg/m³ respirable dust         OSHA PEL (TWA)[1]       0.06 mg/m³ respirable dust         atuminium oxide, non-fibrous (1344-28-1)       USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       1 mg/m² respirable dust         quartz (14808-60-7)       USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV -         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted Average exposure limit 8 h; TLV -         USA - OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust       0.025         Sea Appropriate engineering controls       :       Provide adequate ventilation to minimize dust concentrations.
USA - ACGH*-Occupational Exposure Limits       0.025 mg/m³ respirable dust         USA - OSHA - Occupational Exposure Limits       0.065 mg/m³ respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         atuminium oxide, non-fibrous (1344-28-1)       USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       1 mg/m³ respirable dust         quartz (14808-60-7)       USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - LAGH OCcupational Exposure Limits         Local name       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - USA - OstHA - Occupational Exposure Limits         Local name       Silica, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         AcGH Occupational Exposure Limits       Itag mg/m³ respirable dust         Local name       Silica, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment:       Avoid all unnecessary exposure.         Hand protection:       Wear suitable protective clothing
ACGH OEL TWA       0.025 mg/m³ respirable dust         USA - OSCUPATIONAL Exposure Limits       0.05 mg/m³ respirable dust         aluminium avide, non-fibrous (1344-28-1)       0.05 mg/m³ respirable dust         JUSA - ACGH - Occupational Exposure Limits       ACGH OEL TWA         ACGH OEL TWA       1 mg/m³ respirable dust         quartz (1408-60-7)       1         USA - ACGH - Occupational Exposure Limits       ACGH OEL TWA         ACGH OEL TWA       0.025 mg/m³ (Silca-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable fraction)         USA - ACGH - Occupational Exposure Limits       0.025 mg/m³ respirable dust         Local name       Silica, crystalline quartz, respirable dust         OSHA - Occupational Exposure Limits       0.03 for gr/m³ respirable dust         Local name       Silica, crystalline quartz, respirable dust         OSHA - Occupational Exposure Limits       0.05 mg/m³ respirable dust         Local name       Silica, crystalline quartz, respirable dust         OSHA - Occupational Exposure Limits       1.025 mg/m³ respirable dust         Local name       Silica, crystalline quartz, respirable dust         Cost name       Silica, crystalline quartz, respirable dust         Audi all unnecessary exposures       F         B.1 Individual protection measures/Personal protective equipment
USA - OSHA - Occupational Exposure Limits       0.05 mg/m <sup>2</sup> respirable dust         aluminium oxide, non-fibrous (1344-28-1)       USA - ACCIH - Occupational Exposure Limits         ACGIH OEL TWA       1 mg/m <sup>3</sup> respirable dust         quartz (14808-60-7)       1025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable fraction)         USA - ACCIH - Occupational Exposure Limits       0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable dust         USA - ACCIH OEL TWA       0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable dust         USA - OstHA - Occupational Exposure Limits       0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- IAdopted Value; Respirable dust         USA - SEL (TWA) [1]       0.05 mg/m <sup>3</sup> respirable dust         Colar name       Silica, crystalline quartz, respirable dust         Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.1 Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.2 Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.1 And protective equipment:       Avoid all unnecessary exposure.         Hand protective gloves.       : Provide adequate ventilation to minimize dust
CSHA PEL (TWA) [1]       [0.05 mg/m³ respirable dust         aluminium oxide, non-fibrous (1344-28-1)         USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA       1 mg/m³ respirable dust         quartz (1480-60-7)         USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable fraction)         USA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable dust         Local name       Silica, crystalline quartz, respirable dust         OSHA - Occupational Exposure Limits       1 (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Oth et al. ink or smoke during use.         SECTION 9: Physical
aluminium oxide, non-fibrous (1344-28-1)         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       1 mg/m³ respirable dust         quartz (14808-60-7)         USA - ACGH - Occupational Exposure Limits         ACGH OEL TWA       0.025 mg/m² (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Madpted Value; Respirable fraction)         USA - ACGH - Occupational Exposure Limits       0.026 mg/m² (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Madpted Value; Respirable fraction)         USA - ACGH - Occupational Exposure Limits       0.006 mg/m² (respirable dust         Local name       0.007 mg/m² (Silica-Crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.06 mg/m² respirable dust         B2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B3. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         B2 per
USA - ACGIH - Occupational Exposure Limits       1 mg/m³ respirable dust         ACGIH OL TWA       1 mg/m³ respirable dust         Quartz (14808-60-7)       USA - ACGIH - Occupational Exposure Limits         ACGIH OL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       0.035 mg/m³ (Respirable dust         Local name       Silica, crystalline quartz, respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         91, Information on basic physical and chemical properties<
ACGIH OEL TWA       1 mg/m³ respirable dust         quartz (14808-60-7)         USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Acdopted Value; Respirable fraction)         USA - ACGL       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Acdopted Value; Respirable fraction)         USA - SHA - Occupational Exposure Limits       0.025 mg/m³ (Silica, crystalline quartz; respirable dust         Local name       0.036 mg/m³ respirable dust         OSHA FEL (TWA) [1]       0.06 mg/m² respirable dust         Remark (OSHA)       (3) See Table Z-3.         Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.1. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear appropriate mask         Other information:         Do not eat, dink or smoke during use.         SECTION 9: Physical and chemical properties         Physical state       : Solid         Appear
quartz (14808-60-7)       USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       0.005 mg/m³ (Silica-Crystalline quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       0.05 mg/m³ (Silica-Crystalline quartz; uSA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable dust         QSHA PEL (TWA) [1]       0.06 mg/m³ respirable dust         Remark (OSHA)       [3] See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment       Personal protective equipment:         Avoid all unnecessary exposure.       Hand protection:         Wear protective gloves.       Eye protection:         Chemical goggles or safety glasses       Skin and body protection:         Wear suitable protective clothing       Respiratory protection:         Wear appropriate mask       Other information:         Do not eat, drink or smoke during use.       SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties       Solid         Physical state       : Solid
USA - ACGIH - Occupational Exposure Limits       0.025 mg/m³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       0.025 mg/m³ (Silica, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protection:         Wear suitable protection:         Wear appropriate mask         Other information         Wear appropriate mask         Other information         Den net eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         91/1 Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Grany
ACGIH OEL TWA       0.025 mg/m² (Silca-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV- Adopted Value; Respirable fraction)         USA - OSHA - Occupational Exposure Limits       Silca, crystalline quartz, respirable dust         Local name       Silca, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m² (Silca, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m² (Silca, crystalline quartz, respirable dust         Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray    <
IdSA - Occupational Exposure Limits         Local name       Silica, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m² respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Indivídual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         Physical state       : Soid         Appearance       : Gravy         Odor       : Gravy
USA - OSHA - Occupational Exposure Limits       Silica, crystalline quartz, respirable dust         Local name       Silica, crystalline quartz, respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment       Personal protective equipment:         Avoid all unnecessary exposure.       Hand protection:         Wear protective gloves.       Eye protection:         Chemical goggles or safety glasses       Skin and body protection:         Wear suitable protective clothing       Respiratory protective:         Respiratory protection:       Wear suitable protection:         Wear appropriate mask       Other information:         Do not eat, drink or smoke during use.       Sciid         SECTION 9: Physical and chemical properties       Physical state         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray
Local name       Silica, crystalline quartz, respirable dust         OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protectione clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray
OSHA PEL (TWA) [1]       0.05 mg/m³ respirable dust         Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Avoid all unnecessary exposure.         Hand protection:         Wear protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Remark (OSHA)       (3) See Table Z-3.         8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protectioning         Respiratory protection:         Wear appropriate mask         Other information:         Do to ead, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray
8.2. Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective is gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         Physical state       : Solid         Apperance       : Gray         Odor       : Gray
Appropriate engineering controls       : Provide adequate ventilation to minimize dust concentrations.         8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective is gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         Physical state       : Solid         Apperance       : Gray         Odor       : Gray
8.3. Individual protection measures/Personal protective equipment         Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Oddor       : earthy
Personal protective equipment:         Avoid all unnecessary exposure.         Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Oddor       : earthy
Avoid all unnecessary exposure. Hand protection: Wear protective gloves. Eye protection: Chemical goggles or safety glasses Skin and body protection: Wear suitable protective clothing Respiratory protection: Wear appropriate mask Other information: Do not eat, drink or smoke during use. SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties Physical state  Solid Appearance Color Co
Hand protection:         Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Gray         Odor       : earthy
Wear protective gloves.         Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Oddr       : earthy
Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Eye protection:         Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Chemical goggles or safety glasses         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Wear suitable protective clothing         Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Respiratory protection:         Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Wear appropriate mask         Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Other information:         Do not eat, drink or smoke during use.         SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Do not eat, drink or smoke during use. SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties Physical state : Solid Appearance : Granular mixture. Color : Gray Odor : earthy
SECTION 9: Physical and chemical properties         9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
9.1. Information on basic physical and chemical properties         Physical state       : Solid         Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Physical state     : Solid       Appearance     : Granular mixture.       Color     : Gray       Odor     : earthy
Appearance       : Granular mixture.         Color       : Gray         Odor       : earthy
Color     : Gray       Odor     : earthy
Color     : Gray       Odor     : earthy
Odor threshold · No data available
pH : ≈ 10.5
pH solution concentration : 10 %
Melting point : > 2500 °F
Freezing point : No data available
Boiling point : No data available
Flash point       : No data available         Relative evaporation rate (butyl acetate=1)       : No data available
Flammability (solid, gas) : Not flammable.
Vapor pressure : No data available
Relative vapor density at 20°C : No data available
Relative density $\therefore \approx 2.1$
Solubility : Slightly soluble.
Partition coefficient n-octanol/water (Log Pow) : No data available
Partition coefficient n-octanol/water (Log Pow)       : No data available         Auto-ignition temperature       : No data available
Partition coefficient n-octanol/water (Log Pow): No data availableAuto-ignition temperature: No data availableDecomposition temperature: No data available
Partition coefficient n-octanol/water (Log Pow): No data availableAuto-ignition temperature: No data availableDecomposition temperature: No data availableViscosity, kinematic: Not Applicable

### Safety Data Sheet

Oxidizing properties :	No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	Not classified
	Not classified Not classified
aluminium oxide, non-fibrous (1344-28-1)	
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation :	Causes skin irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 – 7
Serious eye damage/irritation :	Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6-7
aluminium oxide, non-fibrous (1344-28-1)	
рН	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 - 7
Respiratory or skin sensitization :	Not classified

### Safety Data Sheet

Germ cell mutagenicity       : Not classified         Carcinogenicity       : May cause cancer (Inhalation).         quartz (14808-60-7)       IARC group         IARC group       1 - Carcinogenic to humans         Reproductive toxicity       : Not classified         STOT-rengeted exposure       : Not classified         Aspiration hazard       : Not classified         Viscosity, kinematic       : Not classified         Potential Adverse human health effects and symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after sin contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes skin irritation.         SECTION 12: Ecological information       1.2.1. Toxicity         aluminium oxide, non-fibrous (1344-28-1)       > 100 mg/l (96 h, Salmo trutta, Literature study)         LC50 - Fish [1]       > 100 mg/l (48 h, Daphnia magna, Literature study)	iuse
IARC group       1 - Carcinogenic to humans         Reproductive toxicity       : Not classified         STOT-single exposure       : Not classified         STOT-repeated exposure       : Not classified         STOT-repeated exposure       : Not classified         STOT-repeated exposure       : Not classified         Aspiration hazard       : Not classified         Viscosity, kinematic       : Not Applicable         aluminium oxide, non-fibrous (1344-28-1)       Viscosity, kinematic         Viscosity, kinematic       : Danger of serious damage to health by prolonged exposure through inhalation.         symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation. May carcancer by inhalation.         Symptoms/effects after eye contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes eye irritation.         SECTION 12: Ecological information       12.1. Toxicity         aluminium oxide, non-fibrous (1344-28-1)       LC50 - Fish [1]         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	IUSE
Reproductive toxicity       : Not classified         STOT-single exposure       : Not classified         STOT-repeated exposure       : Not classified         Aspiration hazard       : Not classified         Viscosity, kinematic       : Not Applicable         aluminium oxide, non-fibrous (1344-28-1)       Viscosity, kinematic         Viscosity, kinematic       Not applicable (solid)         Potential Adverse human health effects and symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation. May car cancer by inhalation.         Symptoms/effects after skin contact       : Causes skin irritation.         Symptoms/effects after skin contact       : Causes eye irritation.         SECTION 12: Ecological information       : Causes eye irritation.         12.1. Toxicity       aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	iuse
STOT-single exposure       : Not classified         STOT-repeated exposure       : Not classified         Aspiration hazard       : Not classified         Viscosity, kinematic       : Not Applicable         aluminium oxide, non-fibrous (1344-28-1)       Viscosity, kinematic         Viscosity, kinematic       Not applicable (solid)         Potential Adverse human health effects and symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after eye contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes skin irritation.         SECTION 12: Ecological information       : Causes eye irritation.         12.1. Toxicity       aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	iuse
Viscosity, kinematic       Not applicable (solid)         Potential Adverse human health effects and symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation. May carcancer by inhalation.         Symptoms/effects after skin contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes eye irritation.         SECTION 12: Ecological information       12.1. Toxicity         aluminium oxide, non-fibrous (1344-28-1)       > 100 mg/l (96 h, Salmo trutta, Literature study)	iuse
Potential Adverse human health effects and symptoms       : Danger of serious damage to health by prolonged exposure through inhalation.         Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation. May carcer by inhalation.         Symptoms/effects after skin contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes skin irritation.         SECTION 12: Ecological information       : Causes eye irritation.         12.1. Toxicity       aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	iuse
symptoms       Symptoms/effects after inhalation       : Danger of serious damage to health by prolonged exposure through inhalation. May cancer by inhalation.         Symptoms/effects after skin contact       : Causes skin irritation.         Symptoms/effects after eye contact       : Causes eye irritation.         SECTION 12: Ecological information         12.1. Toxicity         aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	iuse
SECTION 12: Ecological information         12.1. Toxicity         aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]         > 100 mg/l (96 h, Salmo trutta, Literature study)	
aluminium oxide, non-fibrous (1344-28-1)         LC50 - Fish [1]       > 100 mg/l (96 h, Salmo trutta, Literature study)	
LC50 - Fish [1] > 100 mg/l (96 h, Salmo trutta, Literature study)	
EC50 - Crustacea [1] > 100 mg/l (48 h. Daphnia magna, Literature study)	
12.2. Persistence and degradability	
Rescocast 17EPC (Mixture)	
Persistence and degradability Not established.	
cristobalite (14464-46-1)	
Persistence and degradability Mineral. Not applicable.	
Chemical oxygen demand (COD) Not applicable	
ThOD Not applicable	
BOD (% of ThOD) Not applicable	
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability Not applicable.	
Chemical oxygen demand (COD) Not applicable	
ThOD Not applicable	
quartz (14808-60-7)	
Persistence and degradability Not applicable.	
Biochemical oxygen demand (BOD) Not applicable	
Chemical oxygen demand (COD) Not applicable	
ThOD Not applicable	
12.3. Bioaccumulative potential	
Rescocast 17EPC (Mixture)	
Bioaccumulative potential Not established.	
cristobalite (14464-46-1)	
Bioaccumulative potential No data available.	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)				
Bioaccumulative potential		No data available.		
quartz (14808-60-7)				
Bioaccumulative potential		No data available.		
12.4. Mobility in soil				
cristobalite (14464-46-1)				
Ecology - soil		No data available.		
aluminium oxide, non-fibr	ous (1344-28-1)			
Surface tension		No data available in the literature		
Ecology - soil		No data available.		
12.5. Other adverse effects				
	Effect on the global warming : None known			
SECTION 13: Disposal considerations				
13.1. Disposal methods				
Product/Packaging disposal reco SECTION 14: Transport		Dispose in a safe manner in accordance with local/national regulations.		
In accordance with DOT Not regulated Transportation of Dangerous Not regulated Transport by sea Not regulated Air transport Not regulated SECTION 15: Regulator 15.1. US Federal regulation All components of this product a (TSCA) inventory	y information	s Active on the United States Environmental Protection Agency Toxic Substances Control Act		
aluminium oxide, non-fibrous (1344-28-1)				
Not subject to reporting requirements of the United States SARA Section 313				
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.			
15.2. International regulations				
CANADA				
Calcium Aluminate Cement (65997-16-2)				
Listed on the Canadian DSL (D	Listed on the Canadian DSL (Domestic Substances List)			
cristobalite (14464-46-1)				
Listed on the Canadian DSL (D	omestic Substances Lis	st)		
aluminium oxide, non-fibr	aluminium oxide, non-fibrous (1344-28-1)			
Listed on the Canadian DSL (D	omestic Substances Lis	st)		
El Degulatione				

EU-Regulations No additional information available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations	
quartz (14808-60-7)	
Listed on IARC (International Agency for Research on	Cancer)
15.3. US State regulations	
Rescocast 17EPC (Mixture)	
U.S California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause
	cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-	1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
-		- Female	- Male		
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 -	No significant risk level (NSRL)	Maximum allowable dose level (MADL)			
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male	( - )	,
Yes	No	No	No		

v Jersey - Right to Know Hazardous		
now) List		
v Jersey - Right to Know Hazardous		
now) List		
nce List		
SECTION 16: Other information		
a		

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date

8/9/2024 : :

Other information	
-------------------	--

Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases				
H315	H315 Causes skin irritation			
H320	Causes eye irritation			
H350	May cause cancer			
Safaty Data Shoat (SDS) USA				

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.