

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Rescoset 90P TR-D3
CAS-No. : Mixture
Product code : 7078
Other means of identification : Alumina-Silicate Wet Chemically Bonded Mortar-Slurry

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory
Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
One Robinson Plaza, Suite 300
6600 Steubenville Pike
Pittsburgh, PA, 15205
United States
T 412-494-4491
SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2B	H320	Causes eye irritation
Carcinogenicity Category 1A	H350	May cause cancer (After drying or heating, Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H315 - Causes skin irritation
H319 - Causes serious eye irritation
H350 - May cause cancer (After drying or heating, Inhalation)
Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear eye protection, protective gloves, protective clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
aluminium oxide, non-fibrous	CAS-No.: 1344-28-1	50 – 75	Not classified
phosphoric acid, conc=75%, aqueous solution	CAS-No.: 7664-38-2	5 – 10	Skin Corr. 1B, H314
quartz	CAS-No.: 14808-60-7	1 – 5	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation. Dust when sawing or tear out.
Symptoms/effects after inhalation	: After drying or heating. Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
Explosion hazard	: Prolonged exposure to fire may cause containers to rupture/explode.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: If spilled, may cause the floor to be slippery.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop release.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes. Avoid contact with skin.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in original container. Keep container closed when not in use.
Incompatible products	: Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Rescoset 90P TR-D3 (Mixture)	
No additional information available	
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³ respirable dust
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	
No additional information available	
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountain with clean water. After drying or heating. Dust when sawing or tear out. Provide adequate ventilation to minimize dust concentrations.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:
Wear protective gloves.
Eye protection:
Chemical goggles or safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Slurry.
Color	: white
Odor	: Acid Odor
Odor threshold	: No data available
pH	: < 3
Melting point	: > 2500 °F
Freezing point	: ≈ 32 °F
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: ≈ 2.4
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: Not Applicable
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Air Setting.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong bases. Avoid contact with materials: such as sulfides and sulfites which could release toxic gases, mixing with strong bases because high heat of reaction can generate steam, and metals which could liberate hydrogen, a flammable gas.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

aluminium oxide, non-fibrous (1344-28-1)

LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

ATE US (oral)	4400 mg/kg body weight
---------------	------------------------

Skin corrosion/irritation : Causes skin irritation.
pH: < 3

aluminium oxide, non-fibrous (1344-28-1)

pH	9 – 10.5 (aqueous suspension, 33 %)
----	-------------------------------------

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

pH	0 – 0.5 (20 °C)
----	-----------------

quartz (14808-60-7)

pH	6 – 7
----	-------

Serious eye damage/irritation : Causes eye irritation.
pH: < 3

aluminium oxide, non-fibrous (1344-28-1)

pH	9 – 10.5 (aqueous suspension, 33 %)
----	-------------------------------------

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

pH	0 – 0.5 (20 °C)
----	-----------------

quartz (14808-60-7)

pH	6 – 7
----	-------

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer (After drying or heating, Inhalation).

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: Not Applicable
aluminium oxide, non-fibrous (1344-28-1)	
Viscosity, kinematic	Not applicable (solid)
Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation. Dust when sawing or tear out.
Symptoms/effects after inhalation	: After drying or heating. Dust when sawing or tear out. Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
SECTION 12: Ecological information	
12.1. Toxicity	
aluminium oxide, non-fibrous (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
12.2. Persistence and degradability	
Rescoset 90P TR-D3 (Mixture)	
Persistence and degradability	Not established.
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	
Persistence and degradability	Biodegradability: not applicable.
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Rescoset 90P TR-D3 (Mixture)	
Bioaccumulative potential	Not established.
aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No data available.
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	
Bioaccumulative potential	No test data of component(s) available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

aluminium oxide, non-fibrous (1344-28-1)

Surface tension	No data available in the literature
Ecology - soil	No data available.

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Ecology - soil	Highly mobile in soil.
----------------	------------------------

12.5. Other adverse effects

Effect on the global warming	: None known
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

aluminium oxide, non-fibrous (1344-28-1)

Not subject to reporting requirements of the United States SARA Section 313

Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.
------	--

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations

CANADA

aluminium oxide, non-fibrous (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

phosphoric acid, conc=75%, aqueous solution (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Rescoset 90P TR-D3 (Mixture)

U.S. - California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov
--	--

quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Rescoset 90P TR-D3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
phosphoric acid, conc=75%, aqueous solution (7664-38-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date

: 8/21/2024

Other information

: Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases	
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.