

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 10/27/2021

Revision date: 10/27/2021

Supersedes: 11/26/2018

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : ST-001 Patching Mix
 CAS-No. : Mixture
 Product code : 1135
 Other means of identification : Alumina-Silicate Wet Air Set Mortar-Slurry

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Refractory
 Recommended use : Industrial use

1.3. Supplier

Resco Products, Inc.
 One Robinson Plaza, Suite 300
 6600 Steubenville Pike
 Pittsburgh, PA 15205 - United States
 412-494-4491

SDS@RescoProducts.com - WWW.RescoProducts.com

1.4. Emergency telephone number

Emergency number : EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300
 Outside USA & Canada +1 703-741-5970

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation Category 2 H315 Causes skin irritation
 Serious eye damage/eye irritation Category 2B H320 Causes eye irritation
 Carcinogenicity Category 1A H350 May cause cancer (After drying or heating, Inhalation)

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
 Hazard statements (GHS US) : H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H350 - May cause cancer (After drying or heating, Inhalation)
 Precautionary statements (GHS US) : P202 - Do not handle until all safety precautions have been read and understood.
 P280 - Wear eye protection, protective gloves, protective clothing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
aluminium oxide, non-fibrous	(CAS-No.) 1344-28-1	20 – 50	Not classified
sodium silicate, alkaline 1.6/2.6, 35%≤concs≤55%, aqueous solutions	(CAS-No.) 1344-09-8	5 – 10	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
cristobalite	(CAS-No.) 14464-46-1	1 – 5	Carc. 1A, H350
quartz	(CAS-No.) 14808-60-7	0.5 – 1	Carc. 1A, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Specific hazards arising from the chemical

Fire hazard	: Not flammable.
-------------	------------------

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: If spilled, may cause the floor to be slippery.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop release.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Avoid contact with eyes. Avoid contact with skin.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in original container. Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ST-001 Patching Mix (Mixture)	
No additional information available	
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)	
No additional information available	
aluminium oxide, non-fibrous (1344-28-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	1 mg/m ³ respirable dust
crystalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	0.025 mg/m ³ respirable dust

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) (mg/m ³)	0.05 mg/m ³ respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	0.025 mg/m ³ (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) (mg/m ³)	0.05 mg/m ³ respirable dust
Remark (OSHA)	(3) See Table Z-3.

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash fountain with clean water.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

After air drying or heating. Dust when sawing or tear out. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Slurry.
Color	: Gray
Odor	: earthy
Odor threshold	: Not applicable
pH	: > 10
Melting point	: > 2500 °F
Freezing point	: ≈ 32 °F
Boiling point	: Not applicable
Critical temperature	: Not applicable
Critical pressure	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: Not applicable
Relative evaporation rate (ether=1)	: Not applicable
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: Not applicable
Vapor pressure at 50 °C	: Not applicable
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Moderately soluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: Not Applicable
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Air Setting.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)

LD50 oral rat	> 2000 mg/kg (Rat, Oral)
---------------	--------------------------

aluminium oxide, non-fibrous (1344-28-1)

LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
---------------	---

LC50 Inhalation - Rat	7.6 mg/l air (Equivalent or similar to OECD 403, 1 h, Rat, Male, Experimental value, Inhalation (aerosol))
-----------------------	--

Skin corrosion/irritation : Causes skin irritation.

pH: > 10

Serious eye damage/irritation : Causes eye irritation.

pH: > 10

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer (After drying or heating, Inhalation).

quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects after inhalation : After drying or heating. May cause cancer by inhalation. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)

LC50 fish 1	210 mg/l (96 h, Brachydanio rerio, Pure substance)
-------------	--

EC50 Daphnia 1	216 mg/l (96 h, Daphnia magna, Pure substance)
----------------	--

12.2. Persistence and degradability

ST-001 Patching Mix (Mixture)

Persistence and degradability	Not established.
-------------------------------	------------------

sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)

Persistence and degradability	Biodegradability: not applicable.
-------------------------------	-----------------------------------

Chemical oxygen demand (COD)	Not applicable
------------------------------	----------------

ThOD	Not applicable
------	----------------

BOD (% of ThOD)	Not applicable
-----------------	----------------

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
crystalobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

ST-001 Patching Mix (Mixture)	
Bioaccumulative potential	Not established.
sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)	
Bioaccumulative potential	No bioaccumulation data available.
aluminium oxide, non-fibrous (1344-28-1)	
Bioaccumulative potential	No data available.
crystalobalite (14464-46-1)	
Bioaccumulative potential	No data available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

sodium silicate, alkaline 1.6/2.6, 35%≤conc≤55%, aqueous solutions (1344-09-8)	
Ecology - soil	No (test) data on mobility of the components available.
aluminium oxide, non-fibrous (1344-28-1)	
Ecology - soil	No data available.
crystalobalite (14464-46-1)	
Ecology - soil	No data available.

12.5. Other adverse effects

Effect on the global warming : None known
Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

ST-001 Patching Mix (Mixture)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

ST-001 Patching Mix

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (1344-28-1)	
Not subject to reporting requirements of the United States SARA Section 313	
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.

15.2. International regulations

CANADA

aluminium oxide, non-fibrous (1344-28-1)	
Listed on the Canadian DSL (Domestic Substances List)	
crystalobalite (14464-46-1)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

quartz (14808-60-7)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

ST-001 Patching Mix (Mixture)					
U.S. - California - Proposition 65 - Other information			This product contains crystalline silica, a chemical known to the state of California to cause cancer. For more information go to WWW.P65Warnings.ca.gov		
crystalobalite (14464-46-1)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		
quartz (14808-60-7)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

Component	State or local regulations
aluminium oxide, non-fibrous (1344-28-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Cristobalite (14464-46-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 10/27/2021
 Other information : Report language name. English. In the event of any conflict between English and other language versions, the English version shall prevail.

Full text of H-phrases:

H315	Causes skin irritation
H320	Causes eye irritation
H350	May cause cancer

SDS US (GHS HazCom 2012)

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.