

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/15/2015 Revision date: 11/11/2024 Supersedes: 11/5/2021

SECTION 1: Identification	
1.1. Identification	
Product form Product name CAS-No. Product code Other means of identification	<ul> <li>Mixture</li> <li>Sureflow 17E</li> <li>Mixture</li> <li>0359</li> <li>Alumina-Silicate Cement Bonded Castable</li> </ul>
1.2. Recommended use and restrictions or	
Use of the substance/mixture	: Refractory
Recommended use	: Industrial use
1.3. Supplier	
Resco Products, Inc. One Robinson Plaza, Suite 300 6600 Steubenville Pike Pittsburgh, PA, 15205 United States T 412-494-4491 SDS@RescoProducts.com - WWW.RescoProducts 1.4. Emergency telephone number	<u>com</u>
Emergency number	: EMERGENCY ONLY (CHEMTREC) USA & Canada 1-800-424-9300 Outside USA & Canada +1 703-741-5970
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mix	ıre
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2B Carcinogenicity Category 1A Full text of H statements : see section 16	H315Causes skin irritationH320Causes eye irritationH350May cause cancer (Inhalation)
2.2. GHS Label elements, including precau	ionary statements
GHS US labeling Hazard pictograms (GHS US)	
Signal word (GHS US) Hazard statements (GHS US) Precautionary statements (GHS US)	<ul> <li>Danger</li> <li>H315 - Causes skin irritation H320 - Causes eye irritation H350 - May cause cancer (Inhalation)</li> <li>P280 - Wear eye protection, Dust respirator, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P260 - Do not breathe dust.</li> </ul>
2.3. Other hazards which do not result in c	assification
No additional information available	
2.4. Unknown acute toxicity (GHS US)	
No additional information available	
SECTION 3: Composition/Information	n ingredients
3.1. Substances	
Not applicable	
3.2. Mixtures	
Name	Product identifier % GHS US classification
Calcium Aluminate Cement	CAS-No.: 65997-16-2 20 – 50 Skin Irrit. 2, H315
aluminium oxide, non-fibrous	Eye Irrit. 2B, H320           CAS-No.: 1344-28-1         10 – 20         Not classified
cristobalite	CAS-No.: 14464-46-1 10 – 20 Carc. 1A, H350
quartz	CAS-No.: 14808-60-7 1 – 5 Carc. 1A, H350

### Safety Data Sheet

Full text of hazard classes and H-statements : see s	section 16
SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact First-aid measures after eye contact	<ul> <li>Gently wash with plenty of soap and water.</li> <li>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present</li> </ul>
	and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.
4.2. Most important symptoms and effects	
Potential Adverse human health effects and symptoms	: Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/effects after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause
Symptoms/effects after skin contact	cancer by inhalation. : Causes skin irritation.
Symptoms/effects after eye contact	: Causes eye irritation.
4.3. Immediate medical attention and spec	
No additional information available	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishin	g media
Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: In case of fire, all extinguishing media allowed.
5.2. Specific hazards arising from the chem	
Fire hazard	: Not flammable.
5.3. Special protective equipment and prec	
Firefighting instructions	: Fight fire with normal precautions from a reasonable distance. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
SECTION 6: Accidental release measu	res
6.1. Personal precautions, protective equip	oment and emergency procedures
6.1.1. For non-emergency personnel	. Do not breathe dust Avoid contact with align and avec
Emergency procedures 6.1.2. For emergency responders	: Do not breathe dust. Avoid contact with skin and eyes.
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area. On land, sweep or shovel into suitable containers.
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containment	• •
Methods for cleaning up	: On land, sweep or shovel into suitable containers. Minimize generation of dust.
6.4. Reference to other sections	tostion
See Heading 8. Exposure controls and personal pro	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Avoid raising dust. Avoid contact with skin and eyes. Do not breathe dust.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
7.2. Conditions for safe storage, including	
Storage conditions Incompatible products	<ul> <li>Store this product in a dry location where it can be protected from the elements.</li> <li>Strong bases. Strong acids.</li> </ul>
SECTION 8: Exposure controls/person	
8.1. Control parameters	
Sureflow 17E (Mixture)	
No additional information available	

### Safety Data Sheet

	· · · · ·
Calcium Aluminate Cement (65997-16-2)	
No additional information available	
cristobalite (14464-46-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> respirable dust
USA - OSHA - Occupational Exposure Limits	0.05 mg/m3 respirable duet
OSHA PEL (TWA) [1]	0.05 mg/m <sup>3</sup> respirable dust
aluminium oxide, non-fibrous (1344-28-1) USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m <sup>3</sup> respirable dust
quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (Silica-Crystalline Quartz; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
USA - OSHA - Occupational Exposure Limits	
	Silica, crystalline quartz, respirable dust
OSHA PEL (TWA) [1]	0.05 mg/m <sup>3</sup> respirable dust
Remark (OSHA)	(3) See Table Z-3.
8.2. Appropriate engineering controls	
	Provide adequate ventilation to minimize dust concentrations.
8.3. Individual protection measures/Personal	protective equipment
Personal protective equipment: Avoid all unnecessary exposure.	
Hand protection:	
Wear protective gloves.	
Eye protection:	
Chemical goggles or safety glasses	
Skin and body protection:	
Wear suitable protective clothing	
Respiratory protection:	
Wear appropriate mask Other information:	
Do not eat, drink or smoke during use.	
SECTION 9: Physical and chemical prope	erties
9.1. Information on basic physical and chemic	
	Solid Crowler mixture
Appearance : Color :	Granular mixture. Light gray
Odor :	earthy
Odor threshold :	No data available
pH :	≈ 10.5
pH solution concentration : Melting point	10 % > 2500 °F
Melting point : Freezing point :	No data available
Boiling point :	No data available
Flash point :	No data available
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Not flammable.
Vapor pressure :	No data available
Relative vapor density at 20°C :	No data available
Relative density : Solubility :	≈ 2.1 Slightly soluble.
Partition coefficient n-octanol/water (Log Pow)	No data available
Auto-ignition temperature	No data available
Decomposition temperature :	No data available
Viscosity, kinematic :	Not Applicable
Viscosity, dynamic : Explosion limits :	No data available No data available
Explosive properties :	No data available

### Safety Data Sheet

9.2. Other information	No data available
No additional information available	
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Hydraulic setting.	
10.2. Chemical stability	
Stable under normal conditions of use.	
10.3. Possibility of hazardous reactions	
Not established.	
10.4. Conditions to avoid	
Avoid dust formation.	
10.5. Incompatible materials	
Strong acids. Strong bases.	
10.6. Hazardous decomposition products	
No additional information available	
SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
	Not classified
	Not classified Not classified
aluminium oxide, non-fibrous (1344-28-1)	
	1
LD50 oral rat	> 15900 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 2.3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation :	Causes skin irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminium oxide, non-fibrous (1344-28-1)	·
Hq	9 – 10.5 (aqueous suspension, 33 %)
·	
quartz (14808-60-7)	
рН	6 – 7
Serious eye damage/irritation :	Causes eye irritation. pH: ≈ 10.5
Calcium Aluminate Cement (65997-16-2)	
рН	≤ 13
cristobalite (14464-46-1)	
рН	6 - 7
aluminium oxide, non-fibrous (1344-28-1)	
pH	9 – 10.5 (aqueous suspension, 33 %)
quartz (14808-60-7)	
рН	6 - 7
Respiratory or skin sensitization :	Not classified

### Safety Data Sheet

	: Not classified
Carcinogenicity quartz (14808-60-7)	: May cause cancer (Inhalation).
IARC group	1 - Carcinogenic to humans
	: Not classified
STOT-single exposure	Not classified
STOT-repeated exposure Aspiration hazard	Not classified
Viscosity, kinematic	Not Applicable
aluminium oxide, non-fibrous (1344-28-1)	
Viscosity, kinematic	Not applicable (solid)
	: Danger of serious damage to health by prolonged exposure through inhalation.
symptoms Symptoms/effects after inhalation	<ul> <li>Danger of serious damage to health by prolonged exposure through inhalation. May cause cancer by inhalation.</li> </ul>
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact SECTION 12: Ecological information	: Causes eye irritation.
12.1. Toxicity	
aluminium oxide, non-fibrous (1344-28-1)	
LC50 - Fish [1]	> 100 mg/l (96 h, Salmo trutta, Literature study)
EC50 - Crustacea [1]	> 100 mg/l (48 h, Daphnia magna, Literature study)
12.2. Persistence and degradability	
Sureflow 17E (Mixture)	
Persistence and degradability	Not established.
cristobalite (14464-46-1)	
Persistence and degradability	Mineral. Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
aluminium oxide, non-fibrous (1344-28-1)	
Persistence and degradability	Not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
quartz (14808-60-7)	
Persistence and degradability	Not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Sureflow 17E (Mixture)	
Bioaccumulative potential	Not established.
cristobalite (14464-46-1)	
Bioaccumulative potential	No data available.
·	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

aluminium oxide, non-fibrous (134	4-28-1)
Bioaccumulative potential	No data available.
quartz (14808-60-7)	
Bioaccumulative potential	No data available.
12.4. Mobility in soil	
cristobalite (14464-46-1)	
Ecology - soil	No data available.
aluminium oxide, non-fibrous (134	4-28-1)
Surface tension	No data available in the literature
Ecology - soil	No data available.
12.5. Other adverse effects	
Effect on the global warming	: None known
SECTION 13: Disposal consider	ations
13.1. Disposal methods	
Product/Packaging disposal recommendat	
SECTION 14: Transport informa In accordance with DOT / TDG / IMDG / IA	
Transportation of Dangerous Goods Not regulated Transport by sea Not regulated Air transport Not regulated	
SECTION 15: Regulatory inform	ation
15.1. US Federal regulations	
All components of this product are presen (TSCA) inventory	at and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act
aluminium oxide, non-fibrous (134	4-28-1)
Not subject to reporting requirements of the	ne United States SARA Section 313
Note	Note: The section 313 chemical list contains "CAS # 1344-28-1 Aluminum Oxide (Fibrous forms)"; the Aluminum oxide contained in this product is non-fibrous, and thus is not a section 313 material. Only manufacturing, processing, or otherwise use of aluminum oxide in the fibrous form triggers reporting.
15.2. International regulations	
CANADA	
Calcium Aluminate Cement (65997	-16-2)
Listed on the Canadian DSL (Domestic S	ubstances List)
cristobalite (14464-46-1)	
Listed on the Canadian DSL (Domestic S	ubstances List)
aluminium oxide, non-fibrous (134	4-28-1)
Listed on the Canadian DSL (Domestic Si	
EU-Regulations	· · · ·

EU-Regulations No additional information available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations	
quartz (14808-60-7)	
Listed on IARC (International Agency for Research on	Cancer)
15.3. US State regulations	
Sureflow 17E (Mixture)	
U.S California - Proposition 65 - Other information	This product contains crystalline silica, a chemical known to the state of California to cause
	cancer. For more information go to WWW.P65Warnings.ca.gov

cristobalite (14464-46-	1)				
U.S California -	U.S California -	U.S California -	U.S California -	No significant risk	Maximum allowable
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	level (NSRL)	dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity	Reproductive Toxicity		
_		- Female	- Male		
Yes	No	No	No		

quartz (14808-60-7)					
U.S California - Proposition 65 -	U.S California - Proposition 65 -		U.S California - Proposition 65 -	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity - Female	Reproductive Toxicity - Male		
Yes	No	No	No		

Component	State or local regulations
Cristobalite (14464-46-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
aluminium oxide, non-fibrous (1344-28-1)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Quartz (14808-60-7)	U.S New Jersey - Right to Know Hazardous Substance List
SECTION 16: Other information	
according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations	

Revision date

Other information

: 11/11/2024

: Re	port language name. English. In the event of any conflict between English and other language
ve	rsions, the English version shall prevail.

Full text of H-phrases			
H315	Causes skin irritation		
H320	Causes eye irritation		
H350 May cause cancer			
Safaty Data S	et (SDS) LISA		

Safety Data Sheet (SDS), USA

This information and recommendations set forth herein are taken from sources believed to be accurate as of the date herein, however, Resco Products, Inc. makes no warranty with respect to the accuracy of the information or the suitability of the recommendations, and assumes no liability to any user thereof.